



velex

CATALOGUE 2025

Durable marine stereo you can trust

Velex Tech Pte Ltd



velex

“

We have prepared this catalogue to provide a comprehensive guide to our product range. However, please call us for up-to-date pricing, latest deals, and new products.



180W
MOFSET POWER
45W X 4

SINGLE DIN
136X51MM

VX565DR

DIGITAL MEDIA RECEIVER



SPECIFICATION

GENERAL		RECEIVER		ENVIRONMENT	
Display	3 inch IPS TFT display	AM/FM	EU/USA switch	Ingress Rating	IPx5
Supply Voltage	10.8-15.6V DC	DAB+	Optional, EU only	Temperature Range	-10 to 60 °C
Current Protect	10 amp 3AG fuse	Media playback	Audio/Video/Photo	MECHANICAL	
Bluetooth	A2DP Ver 5.0	Audio Output	4 x 45W P-P		
MECHANICAL		PREAMP		Auxiliary	3.5mm Jack
Dimension	W159 X H 75 X D80.2mm	Line Out	2V PP	USB Stick	Yes
Weight	770g	BACKLIGHT		Video In/Out	Yes
Mounting Depth	Min 79mm	Level	2	Sub-W	Yes
				2.4G Remote	Optional



180W
MOFSET POWER
45W X 4

SINGLE DIN
136X51MM

VX760D

DIGITAL MEDIA RECEIVER



SPECIFICATION

GENERAL		RECEIVER		ENVIRONMENT	
Display	3 inch Crystal display	AM/FM	EU/USA switch	Ingress Rating	IPx5
Supply Voltage	10.8-15.6V DC	DAB+	Optional, EU only	Temperature Range	-10 to 60 °C
Current Protect	10 amp 3AG fuse	Media playback	WMA/MP3	MECHANICAL	
Bluetooth	A2DP Ver 4.0	Audio Output	4 x 45W P-P		
MECHANICAL		PREAMP		Auxiliary	3.5mm Jack
Dimension	W159 X H 75 X D80.2mm	Line Out	2V PP	USB Stick	Yes
Weight	770g	BACKLIGHT		Video In/Out	No
Mounting Depth	Min 79mm	Level	2	Sub-W	No
				2.4G Remote	Yes



180W
MOFSET POWER
45W X 4



VX526

DIGITAL MEDIA RECEIVER



SPECIFICATION

GENERAL		RECEIVER		ENVIRONMENT	
Display	3 inch IPS TFT display	AM/FM	EU/USA switch	Ingress Rating	IPx5
Supply Voltage	10.8-15.6V DC	DAB+	Optional,EU only	Temperature Range	-10 to 60 °C
Current Protect	10 amp 3AG fuse	Media playback	Audio/Video/Photo	MECHANICAL	
Bluetooth	A2DP Ver 5.0	Audio Output	4 x 45W P-P		
MECHANICAL		PREAMP			
Dimension	W115 X H106 X 106mm	Line Out	2V PP	Auxiliary	3.5mm Jack
Weight	810g	BACKLIGHT		USB Stick	Yes
Mounting Depth	Min 85mm			Video In/Out	Yes
				Sub-W	Yes
		Level	2	2.4G Remote	Optional



180W
MOFSET POWER
45W X 4



VX720

DIGITAL MEDIA RECEIVER



SPECIFICATION

GENERAL		RECEIVER		ENVIRONMENT	
Display	3 inch Crystal display	AM/FM	EU/USA switch	Ingress Rating	IPx5
Supply Voltage	10.8-15.6V DC	DAB+	Optional,EU only	Temperature Range	-10 to 60 °C
Current Protect	10 amp 3AG	Media playback	WMA/MP3	MECHANICAL	
Bluetooth	A2DP Ver 4.0	Audio Output	4 x 45W P-P		
MECHANICAL		PREAMP			
Dimension	L115 X W106 X H106mm	Line Out	2V PP	Auxiliary	3.5mm Jack
Weight	770g	BACKLIGHT		USB Stick	Yes
Mounting Depth	Min 85mm			Video In/Out	No
				Sub-W	No
		Level	2	2.4G Remote	Yes



UP3 **180W**
MOFSET POWER
45W X 4

**DIGITAL MEDIA
RECEIVER**



UP5 **180W**
MOFSET POWER
45W X 4

**DIGITAL MEDIA
RECEIVER**



SPECIFICATION

GENERAL		RECEIVER		ENVIRONMENT	
Display	3 inch IPS TFT display	AM/FM	EU/USA switch	Ingress Rating	IPx5
Supply Voltage	10.8-15.6V DC	DAB+	No	Temperature Range	-10 to 60 °C
Current Protect	10 amp fuse	Media playback	Audio/Video/Photo	MECHANICAL	
Bluetooth	A2DP Ver 5.0	Audio Output	4 x 45W P-P	Auxiliary	3.5mm Jack
MECHANICAL		PREAMP		USB Stick	Yes
Dimension	W115 X H106 X 106mm	Line Out	2V PP	Video In/Out	Video in
Weight	810g	BACKLIGHT		Sub-W	Yes
Mounting Depth	Min 85mm	Level	2	2.4G Remote	No



180W
MOFSET POWER
45W X 4

VX280

DIGITAL MEDIA RECEIVER



SPECIFICATION

GENERAL		RECEIVER		ENVIRONMENT	
Display	2.5 inch Crystal display	AM/FM	EU/USA switch	Ingress Rating	IPx5
Supply Voltage	10.8-15.6V DC	DAB+	No	Temperature Range	-10 to 60 °C
Current Protect	10 amp fuse	Media playback	WMA/MP3	MECHANICAL	
Bluetooth	A2DP Ver 5.0	Audio Output	4 x 45W P-P		
MECHANICAL		PREAMP			
Dimension	W155 X H105 X D68.5mm	Line Out	2V PP	Auxiliary	3.5mm Jack
Weight	670g	BACKLIGHT		USB Stick	Yes
Mounting Depth	Min 68.5 mm			Video In/Out	No
		Level	2	Sub-W	No
				2.4G Remote	No



180W
MOFSET POWER
45W X 4

SINGLE DIN
136X51MM

VX600

DIGITAL MEDIA RECEIVER



SPECIFICATION

GENERAL		RECEIVER		ENVIRONMENT	
Display	4 inch IPS TFT display	AM/FM	EU/USA switch	Ingress Rating	IPx5
Supply Voltage	10.8-15.6V DC	DAB+	Optional,EU only	Temperature Range	-10 to 60 °C
Current Protect	10 amp 3AG fuse	Media playback	Audio/Video/Photo	MECHANICAL	
Bluetooth	A2DP Ver 4.0	Audio Output	4 x 45W P-P		
MECHANICAL		PREAMP			
Dimension	W172 X H 90 X D86mm	Line Out	2V PP	Auxiliary	3.5mm Jack
Weight	1100g	BACKLIGHT		USB Stick	Yes
Mounting Depth	Min 79mm			Video In/Out	Yes
		Level	2	Sub-W	Yes
				2.4G Remote	No



180W
MOFSET POWER
45W X 4

VX502

MARINE AMPLIFIER



SPECIFICATION

GENERAL		RECEIVER		ENVIRONMENT	
Display	No	AM/FM	No	Ingress Rating	IPx5
Supply Voltage	10.8-15.6V DC	DAB+	No	Temperature Range	-10 to 60 °C
Current Protect	10 amp 3AG	Media playback	WMA/MP3	MECHANICAL	
Bluetooth	A2DP Ver 5.0	Audio Output	4 x 45W P-P	Auxiliary	RCA in
MECHANICAL		PREAMP		USB Stick	Yes
Dimension	L204 X W99 X H51mm	Line Out	2V PP	Video In/Out	No
Weight	920g	BACKLIGHT		Sub-W	No
Remote size	L82.5 x W42.3 X H13 mm	Level	No	2.4G Remote	No



240W
CLASS D
60W X 4

VX505

MARINE AMPLIFIER



SPECIFICATION

GENERAL		RECEIVER		ENVIRONMENT	
Display	No	AM/FM	No	Ingress Rating	IPx5
Supply Voltage	10.8-15.6V DC	DAB+	No	Temperature Range	-10 to 60 °C
Current Protect	10 amp fuse	Media playback	WMA/MP3	MECHANICAL	
Bluetooth	A2DP Ver 5.0	Audio Output	4 x 60W P-P	Auxiliary	RCA in
MECHANICAL		PREAMP		USB Stick	Yes
Dimension	L204 X W99 X H51mm	Line Out	2V PP	Video In/Out	No
Weight	970g	BACKLIGHT		Sub-W	No
Remote Size	L82.5 x W42.3 X H13 mm	Level	No	2.4G Remote	No



180W
MOFSET POWER
45W X 4

VX402

MARINE AMPLIFIER



SPECIFICATION

GENERAL		RECEIVER		ENVIRONMENT	
Display	No	AM/FM	No	Ingress Rating	IPx5
Supply Voltage	10.8-15.6V DC	DAB+	No	Temperature Range	-10 to 60 °C
Current Protect	10 amp fuse	Media playback	WMA/MP3	MECHANICAL	
Bluetooth	A2DP Ver 5.0	Audio Output	4 x 45W P-P	Auxiliary	RCA in
MECHANICAL		PREAMP		USB Stick	Yes
Dimension	L150 X W99 X H 50mm	Line Out	2V PP	Video In/Out	No
Weight	650g	BACKLIGHT		Sub-W	No
Remote Size	L80 X W47 X H22mm	Level	No	2.4G Remote	Yes



300W
MOFSET POWER
150W X 2

VX508

MARINE AMPLIFIER



SPECIFICATION

GENERAL		RECEIVER		ENVIRONMENT	
Display	No	AM/FM	No	Ingress Rating	IPx5
Supply Voltage	10.8-15.6V DC	DAB+	No	Temperature Range	-10 to 60 °C
Current Protect	20 amp fuse	Media playback	WMA/MP3	MECHANICAL	
Bluetooth	A2DP Ver 5.0	Audio Output	2 x 150W P-P	Auxiliary	RCA in
MECHANICAL		PREAMP		USB Stick	Yes
Dimension	L204 X W99 X H51mm	Line Out	No	Video In/Out	No
Weight	1020g	BACKLIGHT		Sub-W	No
Remote size	L82.5 x W42.3 X H13 mm	Level	No	2.4G Remote	No



240W
CLASS D
60W X 4

TT405

MARINE AMPLIFIER



SPECIFICATION

GENERAL		RECEIVER		ENVIRONMENT	
Display	No	AM/FM	No	Ingress Rating	IPx5
Supply Voltage	10.8-15.6V DC	DAB+	No	Temperature Range	-10 to 60 °C
Current Protect	10 amp 3AG	Media playback	WMA/MP3	MECHANICAL	
Bluetooth	A2DP Ver 5.0	Audio Output	4 x 60W P-P		
MECHANICAL		PREAMP		Auxiliary	RCA in
Dimension	L204 X W99 X H51mm	Line Out	2V PP	USB Stick	Yes
Weight	970g	BACKLIGHT		Video In/Out	No
Remote size	W25.5 X L49.3			Sub-W	No
		Level	No	2.4G Remote	No



VX208

MARINE STEREO



SPECIFICATION

GENERAL		RECEIVER		ENVIRONMENT	
Display	No	AM/FM	No	Ingress Rating	IPx5
Supply Voltage	10.8-15.6V DC	DAB+	No	Temperature Range	-10 to 60 °C
Current Protect	10 amp fuse	Media playback	WMA/MP3	MECHANICAL	
Bluetooth	A2DP Ver 4.0	Audio Output	2 Channels		
MECHANICAL		PREAMP		Auxiliary	3.5mm Jack
Dimension	W96 X L96mm	Line Out	2V	USB Stick	Yes
Weight	700g	BACKLIGHT		Video In/Out	No
Mounting Depth	Min 89mm			Sub-W	No
		Color	3	2.4G Remote	No



TT405S

MARINE AMPLIFIER

TT405SW

MARINE AMPLIFIER



240W
CLASS D
60W X 4

SPECIFICATION

GENERAL		RECEIVER		ENVIRONMENT	
Display	No	AM/FM	No	Ingress Rating	IPx5
Supply Voltage	10.8-15.6V DC	DAB+	No	Temperature Range	-10 to 60 °C
Current Protect	10 amp fuse	Media playback	WMA/MP3	MECHANICAL	
Bluetooth	A2DP Ver 5.0	Audio Output	4 x 60W P-P		
MECHANICAL		PREAMP		Auxiliary	RCA in
Dimension	L201XW99 X H51 mm	Line Out	2V PP	USB Stick	Yes
Weight	970g	BACKLIGHT		Video In/Out	No
Remote Size	W25.5 X L49.3	Level	No	Sub-W	No
				2.4G Remote	No



TT408

MARINE STEREO

TT408W

MARINE STEREO



SPECIFICATION

GENERAL		RECEIVER		ENVIRONMENT	
Display	No	AM/FM	No	Ingress Rating	IPx5
Supply Voltage	10.8-15.6V DC	DAB+	No	Temperature Range	-10 to 60 °C
Current Protect	10 amp fuse	Media playback	WMA/MP3	MECHANICAL	
Bluetooth	A2DP Ver 4.0	Audio Output	2 Channels		
MECHANICAL		PREAMP		Auxiliary	3.5mm Jack
Dimension	W96 x L96mm	Line Out	600mV	USB Stick	Yes
Weight	400g	BACKLIGHT		Video In/Out	No
Mounting Depth	Min 89 mm	Color	3	Sub-W	No
				2.4G Remote	No



TT408S

MARINE STEREO

TT408SW

MARINE STEREO



SPECIFICATION

GENERAL		RECEIVER		ENVIRONMENT	
Display	No	AM/FM	No	Ingress Rating	IPx5
Supply Voltage	10.8-15.6V DC	DAB+	No	Temperature Range	-10 to 60 °C
Current Protect	10 amp fuse	Media playback	WMA/MP3	MECHANICAL	
Bluetooth	A2DP Ver 5.0	Audio Output	2 Channels		
MECHANICAL		PREAMP		Auxiliary	3.5mm Jack
Dimension	W89X L96 mm	Line Out	600mV	USB Stick	Yes
Weight	400g	BACKLIGHT		Video In/Out	No
Mounting Depth	Min 89 mm	Color	3	Sub-W	No
				2.4G Remote	No



VX150
MARINE STEREO



VX163
MARINE STEREO



180W
MOFSET POWER
45W X 4



SPECIFICATION

GENERAL		RECEIVER		ENVIRONMENT	
Display	2 inch Crystal display	AM/FM	EU/USA switch	Ingress Rating	IPx5
Supply Voltage	10.8-15.6V DC	DAB+	Optional, EU only	Temperature Range	-10 to 60 °C
Current Protect	10 amp fuse	Media playback	WMA/MP3	MECHANICAL	
Bluetooth	A2DP Ver 4.0	Audio Output	4 x 45W P-P	Auxiliary	3.5mm Jack
MECHANICAL		PREAMP		USB Stick	Yes
Dimension	W89 X D 105 mm	Line Out	2V PP	Video In/Out	No
Weight	680g	BACKLIGHT		Sub-W	No
Mounting Depth	Min 98 mm	Level	2	2.4G Remote	No



VX150W
MARINE STEREO



VX163W
MARINE STEREO



180W
MOFSET POWER
45W X 4

GAUGE
80MM

SPECIFICATION

GENERAL		RECEIVER		ENVIRONMENT	
Display	2 inch Crystal display	AM/FM	EU/USA switch	Ingress Rating	IPx5
Supply Voltage	10.8-15.6V DC	DAB+	Optional, EU only	Temperature Range	-10 to 60 °C
Current Protect	10 amp fuse	Media playback	WMA/MP3	MECHANICAL	
Bluetooth	A2DP Ver 4.0	Audio Output	4 x 45W P-P		
MECHANICAL		PREAMP		Auxiliary	3.5mm Jack
Dimension	W89 X D 105 mm	Line Out	2V PP	USB Stick	Yes
Weight	680g	BACKLIGHT		Video In/Out	No
Mounting Depth	Min 98 mm	Level	2	Sub-W	No
				2.4G Remote	No



VX150S
MARINE STEREO



VX150SW
MARINE STEREO



DUST
INTRUSION



SALT FOG
PROOF



HUMIDITY
RESISTANT



UV
RESISTANT



VIBRATION
PROOF



WATER JET
RESISTANT

180W
MOFSET POWER
45W X 4



GAUGE
80MM

SPECIFICATION

GENERAL		RECEIVER		ENVIRONMENT	
Display	2 inch Crystal display	AM/FM	EU/USA switch	Ingress Rating	IPx5
Supply Voltage	10.8-15.6V DC	DAB+	Optional, EU only	Temperature Range	-10 to 60 °C
Current Protect	10 amp fuse	Media playback	WMA/MP3	MECHANICAL	
Bluetooth	A2DP Ver 4.0	Audio Output	4 x 45W P-P	Auxiliary	3.5mm Jack
MECHANICAL		PREAMP		USB Stick	Yes
Dimension	W89 X D 105 mm	Line Out	2V PP	Video In/Out	No
Weight	680g	BACKLIGHT		Sub-W	No
Mounting Depth	Min 98 mm	Level	2	2.4G Remote	No



VX158

MARINE STEREO



VX168

MARINE STEREO



180W
MOFSET POWER
45W X 4



SPECIFICATION

GENERAL		RECEIVER		ENVIRONMENT	
Display	2 inch Crystal display	AM/FM	EU/USA switch	Ingress Rating	IPx5
Supply Voltage	10.8-15.6V DC	DAB+	Optional, EU only	Temperature Range	-10 to 60 °C
Current Protect	10 amp fuse	Media playback	WMA/MP3	MECHANICAL	
Bluetooth	A2DP Ver 4.0	Audio Output	4 x 45W P-P		
MECHANICAL		PREAMP		Auxiliary	3.5mm Jack
Dimension	L110 X W112 X H110mm	Line Out	2V PP	USB Stick	Yes
Weight	770g	BACKLIGHT		Video In/Out	No
Mounting Depth	Min 85 mm	Level	2	Sub-W	No
				2.4G Remote	No



VX168S
MARINE STEREO



VX168SW
MARINE STEREO



180W
MOFSET POWER
45W X 4



SPECIFICATION

GENERAL

Display	2 inch Crystal display
Supply Voltage	10.8-15.6V DC
Current Protect	10 amp fuse
Bluetooth	A2DP Ver 4.0

MECHANICAL

Dimension	L110 X W112 X H110mm
Weight	770g
Mounting Depth	Min 85 mm

RECEIVER

AM/FM	EU/USA switch
DAB+	Optional, EU only
Media playback	WMA/MP3
Audio Output	4 x 45W P-P

PREAMP

Line Out	2V PP
----------	-------

BACKLIGHT

Level	2
-------	---

ENVIRONMENT

Ingress Rating	IPx5
Temperature Range	-10 to 60 °C

MECHANICAL

Auxiliary	3.5mm Jack
USB Stick	Yes
Video In/Out	No
Sub-W	No
2.4G Remote	No



VX230W
MARINE STEREO



VX230B
MARINE STEREO



VX230G
MARINE STEREO



180W
MOFSET POWER
45W X 4



SPECIFICATION

GENERAL		RECEIVER		ENVIRONMENT	
Display	2.4 inch Crystal display	AM/FM	EU/USA switch	Ingress Rating	IPx5
Supply Voltage	10.8-15.6V DC	DAB+	No	Temperature Range	-10 to 60 °C
Current Protect	10 amp fuse	Media playback	WMA/MP3	MECHANICAL	
Bluetooth	A2DP Ver 5.0	Audio Output	4 x 45W P-P		
MECHANICAL		PREAMP		Auxiliary	3.5mm Jack
Dimension	W105 X D64 mm	Line Out	2V PP	USB Stick	Yes
Weight	500g	BACKLIGHT		Video In/Out	No
Mounting Depth	Min 70 mm	Level	No	Sub-W	No
				2.4G Remote	No



VX100GR
MARINE STEREO



VX100BK
MARINE STEREO



VX110
MARINE STEREO



180W
MOFSET POWER
45W X 4



SPECIFICATION

GENERAL		RECEIVER		ENVIRONMENT	
Display	1.8 inch Crystal display	AM/FM	EU/USA switch	Ingress Rating	IPx5
Supply Voltage	10.8-15.6V DC	DAB+	No	Temperature Range	-10 to 60 °C
Current Protect	10 amp Fuse	Media playback	WMA/MP3	MECHANICAL	
Bluetooth	A2DP Ver 5.0	Audio Output	4 x 45W P-P	Auxiliary	3.5mm Jack
MECHANICAL		PREAMP		USB Stick	Yes
Dimension	W105 X D64 mm	Line Out	2V PP	Video In/Out	No
Weight	500g	BACKLIGHT		Sub-W	No
Mounting Depth	Min 70 mm	Level	No	2.4G Remote	No



Velex Tech Pte Ltd

3F, Bldg A, Zhenduoli Industry Park, 2 Baotian Road, Xinsheng,
Longgang, Shenzhen, China

Tel: (86) 755-82713756
Mob: (86) 13602557806
Fax: (86) 755-83067050

hauer@velextech.com

Velex Tech Pte Ltd.

All specifications are subject to change without notice. Copyright© 2025 Velex.
The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc.
and any use of such marks by Velex is under license